LED-Teva slim

OPEN-HOUSING LUMINAIRE





Open-housing LED luminaire for industrial and public premises



Operating conditions

Typical applications of LED-Teva slim include large and high spaces, like stores, warehouses and industrial spaces, but it is applicable for all kinds of new installations and renovation installments, where a lot of light is needed.



Installation and maintenance

LED-Teva slim can be installed on ceiling surfaces or on suspension rails. The luminaire does not contain separate ballasts, so in addition to normal cleaning, it doesn't require other maintenace than replacing the LED tube when the lifetime has come to its end. Valtavalo LED tubes can be installed and replaced without any electrical work.



Long lifetime

LED-Teva slim is designed for I-3 LED tubes, and the amount of light is easily regulated by adding or removing LED tubes. For maximum lifetime, LED-Teva slim can be equipped with extremely long-lasting Valtavalo LED tubes.

LED-Teva slim

OPEN-HOUSING LUMINAIRE



Technical specifications

Model	LED-Teva slim 120cm	LED-Teva slim 150cm			
Weight (kg)	1,6	2			
Dimensions (length x width x height, mm)	1223 × 122 × 71	1523 × 122 × 71			
Socket Type	T8/GI3				
Input Voltage	230 V AC, 50/60 Hz				
Protection	IP20				
Housing Material	White powder coated steel				
Warranty	5 years				
Connection	5-pole screwless terminal block (2 pcs.), 5 × 2,5 mm² Through-wired by default Feed-throughs at both ends of the luminaire				
Installation	Ceiling surface, suspension rail				
Additional information	Applicable for LED tubes only, can not be used with traditional fluorescent tubes. Light distribution data (Eulumdat files) available for lighting design (downloadable at: http://valtavalo.fi/tuotteet-cpt/led-teva-3/?lang=en)				

Performance with Valtavalo G3+ LED tubes

Length of the tube	120	cm cm	150 cm		
Power	3 × I	9 W	3 × 24 W		
Colour Temperature	400	OOK	4000K		
Cover	Semiopal	Clear	Semiopal	Clear	
Rated Luminous Flux	7 000 lm	7 400 lm	8 800 lm	9 300 lm	

Performance with Valtavalo G4 LED tubes

Length of the tube	120 cm		150 cm		150 cm	
Power	3 × 19 W		3 × 24 W		3 × 28 W	
Colour Temperature	4 000 K		4 000 K		4 000 K	
Cover	Semiopal	Clear	Semiopal	Clear	Semiopal	Clear
Rated Luminous Flux	7 000 lm	7 400 lm	8 800 lm	9 300 lm	9 700 lm	10 200 lm

^{*} Valtavalo LED-tubes to be ordered separately.